



Dr. A. Kuntze GmbH

Fon +49 (0) 2150 70 66 -0 | Fax +49 (0) 2150 70 66 -60 Info@kuntze.com | www.kuntze.com



# DOUBLE AND DIFFERENCE MEASUREMENT...

# SINGLE PARAMETER MEASUREMENT...



## dialog. Versatile meter and controller...

Large graphical display, trend indication, log book, text menu. Two PID controllers, three analog outputs, and serial interface.

### Redundance spells security...

Reliable process control. With the dialog's double measurement function you will immediately recognise sensor faults.

### Ratio spells efficiency...

Surveillance of treatment processes. Monitor the efficiency of your ion exchangers via conductivity reduction using the dialog´s difference measurement function.

#### Combination spells compensation...

Independence of interferences. For disinfection with Chlorine, the pH value plays an important role. With the dialog you can measure and control Chlorine and pH simultaneously, and automatically compensate the pH influence on the Chlorine measurement.



dialog

## K 100. Purposive meter and controller...\_

For the purposive measurement and control of a single parameter, the K 100 is the right choice. With temperature measurement and compensation, bidirectional PI controller with alarm function, one analog output and optionally serial interface.

#### Easy operation...

Text menu. Text messages for status and alarm. Indication of controller relay status. Simple manual operation of the relays.

#### Value for money...

Analog output, controller with two relays, additional alarm relay, external controller stop, and much more – all inclusive and ready-to-use.

#### Fits in very well...

Choose between wall-mounting housing with IP65 and panel-mounting housing 96x96mm.

⊕ K 100

| 0.21 | № 21.9°C |
| 0.21 | № 21.9°

K 100 panel-mounting version





K 100